(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 15 September 2005 (15.09.2005)

PCT

(10) International Publication Number WO 2005/084451 A1

(51) International Patent Classification7: A23L 3/18, B01D 5/00

A23C 3/037,

(21) International Application Number:

PCT/SE2005/000324

(22) International Filing Date: 3 March 2005 (03.03.2005)

(25) Filing Language:

English

(26) Publication Language:

English .

(30) Priority Data: 0400520-3

3 March 2004 (03.03.2004) SE

- (71) Applicant (for all designated States except US): TETRA LAVAL HOLDINGS & FINANCE SA [CH/CH]; Avenue Général-Guisan 70, CH-1009 Pully (CH).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): RINGSTRÖM, Roland [SE/SE]; Pärongatan 2, S-240 14 Veberöd (SE).

- (74) Agent: BRUNNSTRÖM, Gunilla; AB Tetra Pak, Patent Department, Ruben Rausings gata, S-221 86 Lund (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: AN APPARATUS FOR THE EVAPORATIVE COOLING OF A LIQUID PRODUCT

(57) Abstract: The disclosure relates to an apparatus for the evaporative cooling of a liquid product. The apparatus comprises a vacuum chamber (1) which is divided into a first, centrally positioned space (6) and a second space (7) which concentrically surrounds the first space (6). Both of the spaces (6, 7) are open towards the upper end wall (2) of the vacuum chamber (1). The first space (6) has an outlet (25) for condensed steam. The second space (7) has an inlet (11) for steamed product, as well as an outlet (12) for the product. The apparatus also includes a circulation circuit for coolant liquid. The first space (6) is extended downwards so that it extends at least as far below the bottom end wall (4) of the vacuum chamber (1) as the extent of the space (6) inside the vacuum chamber (1).

WO 2005/084451 A1 IIII